

# AquaZero 2,70

## Small / Table Cooler I open system



The small refrigerators are compact and easily connect to an existing pipeline system. They are equipped with a water tank and centrifugal pump. In outlet temperatures below + 10 ° C is the use of antifreeze (glycol, 34%) required.

### Technical specifications:

#### Cooling capacity at water inlet / outlet and ambient temperature:

- **Cooling capacity:** **3.00 kW**  
15 ° C / 20 ° C supply / return, 32 ° C outside temp.
- Operating range Cold water inlet temperature: -5 ° C \* to + 15 ° C
- Operating range outside air temperature: + 5 ° C - + 42 ° C
- Refrigerant: R134a
- CO<sup>2</sup> equivalent: 2.02
- Tightness test: NO required \*\*

#### Electrical data:

- Voltage: 230V
- Connection cable: 4m rubber cable with plug
- Power consumption 15/32 ° C: 2.0 kW
- Rated power: 2.3 kW
- Rated current: 13.0 A
- Setpoint constancy: +/- 1K

#### Sounds:

- Noise pressure level: 66 db (A) \*\*\*

#### Air-cooled version:

- Air flow: 2.400 m<sup>3</sup> / h
- Water tank capacity: 28 liters
- Pump pressure: 3.0 bar
- Water volume flow: 0.51 m<sup>3</sup> / h
- Pipe connection: Rp 1/2 " external thread
- Bypass valve with pressure gauge: included
- Dirt trap in the cooling circuit: included
- Float switch f. Wassermangelvoralarm: included

#### Dimensions:

- Length: 1.000 mm
- Width: 520 mm
- Height of floor space: 470 mm
- Footprint: 0.52 m<sup>2</sup>
- Housing: steel sheets, powder-coated
- Weight, unfilled: 150 kg
- Weight, filled: 190 kg

Danger! Note that when used with water, an inhibitor is added which protects the system parts against corrosion. When operating with water there is a risk of freezing, that is why we recommend to use food safe glycol as antifreeze. This already contains the Inhibitor. The mixing ratio should be 34% glycol to 66% water.

All other liquids or additives are not permitted!

\* without condensation protection!

\*\* according to F-Gas Ordinance No. 517 / 20141.1.2015

\*\*\* 1 m distance in free field and 1.2 m height (according to DIN) (tol +/- 1db (A))